

OWS ATF 6-Speed

Fully Synthetic Automatic Transmission Fluid

OWS ATF 6-Speed is a Fully-Synthetic Automatic Transmission Fluid (ATF) specially developed for a the use in state of the art 6-Speed automatic transmissions.

OWS ATF 6-Speed is manufactured using the highest quality Synthetic base stocks and state of the art Überclean® additive technology. This ensures a finished product with an unmatched performance level.

OWS ATF 6-Speed fulfills or exceeds the following specifications:

Mercon SP / LV
BMW M-1375.4
BMW 83220142516
Hyundai 040000C90SG
Jaguar 8432
Land Rover TYK 500050
VW G 055 005
ZF TE-ML 11

Test	Method	Unit	Result
Density @15°C	ASTM D4052	kg / L	0.850
Kinematic Viscosity @40°C	ASTM D445	cSt	31.1
Kinematic Viscosity @100°C	ASTM D445	cSt	6.1
Viscosity Index	ASTM D2270		148
Flash Point, COC	ASTM D92-05A	°C	> 200
Pour Point	ASTM D97	°C	< -45

Typical properties are typical of those obtained with normal production tolerance and do not constitute a specification. All the information contained in this document is considered accurate as of date of printing and no warranty of representation, expressed or implied is made as to the accuracy of the data and information in this publication. The information contained herein is subject to change without notice.