

OWS GrandSport DPF SAE 5W-30

Fully Synthetic Engine Oil for Diesel and Gasoline Engines with or without Turbo

OWS GrandSport DPF SAE 5W-30 is a fully synthetic PAO based formulation that protects against friction, heat and corrosion, keeping engines healthy and efficient. OWS Überclean® additive technology reduces carbon or sludge build up even under severe driving conditions.

OWS GrandSport DPF SAE 5W-30 is manufactured using the highest quality Fully Synthetic base stocks and state of the art Überclean® additive technology. This ensures a finished product with an unmatched performance level.

OWS GrandSport DPF SAE 5W-30 is designed for advanced passenger car gasoline and diesel engines, both turbocharged and non-turbo-charged including engines with diesel particle filters (ACEA C3)

OWS GrandSport DPF SAE 5W-30 fulfills or exceeds the following specifications:

ACEAA3 / B4-04 / C3

API SM /CF

BMW Longlife-04 (OEM Approval)

MB 229.51

Porsche C30

VW 504 00 / 507 00 (OEM Approval)

Test	Method	Unit	Result
Density @15°C	ASTM D4052	kg / L	0.850
Kinematic Viscosity @40°C	ASTM D445	cSt	72.5
Kinematic Viscosity @100°C	ASTM D445	cSt	11.8
Viscosity Index	ASTM D2270		158
Flash Point, COC	ASTM D92-05A	°C	230
Pour Point	ASTM D97	°C	-39

Typical properties are typical of those obtained with normal production tolerance and do not constitute a specification.

All the information contained in this document is considered accurate as of date of printing and no warranty of representation, expressed or implied is made as to the accuracy of the data and information in this publication. The information contained herein is subject to change without notice.