

OWS Multilight SAE 5W-40

Advanced High Performance Fully Synthetic Engine Oil

OWS Multilight SAE 5W-40 Fully Synthetic formulation protects against friction, heat and corrosion, keeping engines healthy and efficient. OWS Überclean® additives reduce carbon and sludge build up even under severe driving conditions.

OWS Multilight SAE 5W-40 has an excellent range of applications; ranging from K class engines to WTI / VTEC engines to European engines. Appropriate for use in turbo-charged car giving improved engines quietness and reduced emissions. Sustained horsepower and torque throughout the life of your engine with regular use.

OWS Multilight SAE 5W-40 is manufactured using the highest quality Fully Synthetic base stocks and state of the art Überclean® technology. This ensures a finished product with an unmatched performance level.

OWS Multilight SAE 5W-40 fulfills or exceeds the following specifications:

ACEAA3 / B3 / B4

API SN/CF

MB 229.5

BMW Longlife-01

VW 502 00 / 505 00 (OEM Approval)

| Test | Method | Unit | Result |
|----------------------------|--------------|--------|--------|
| Density @15°C | ASTM D4052 | kg / L | 0.850 |
| Kinematic Viscosity @40°C | ASTM D445 | cSt | 86.0 |
| Kinematic Viscosity @100°C | ASTM D445 | cSt | 14.0 |
| Viscosity Index | ASTM D2270 | | 168 |
| Flash Point, COC | ASTM D92-05A | °C | > 200 |
| Pour Point | ASTM D97 | °C | < -45 |

Typical properties are typical of those obtained with normal production tolerance and do not constitute a specification.

All the information contained in this document is considered accurate as of date of printing and no warranty of representation, expressed or implied is made as to the accuracy of the data and information in this publication. The information contained herein is subject to change without notice.