

OWS ATF DSG II

Fully Synthetic Dual Clutch Transmission Fluid

OWS ATF DSG II is a Dual Clutch Transmission Fluid formulated on Synthetic Base Stocks,

OWS ATF DSG II is manufactured using the highest quality Synthetic Base Stocks and state of the art Überclean® additive technology. This ensures a finished product with an unmatched performance level.

OWS ATF DSG II fulfills or exceeds the following specifications:

Ford WSS-M2C936-A

BMW DCTF-1/FFL-4/MTF-5

Chrysler 68044345EA

MB 236.21

Mitsubishi Dia Queen SSTF-I

Porsche 999.917.080.00

PSA 9734.S2

Volvo 1161838/1161839

VW/Audi G 052 182 / G 052 529

| Test | Method | Unit | Result |
|----------------------------|--------------|--------|--------|
| Density @15°C | ASTM D4052 | kg / L | 0.849 |
| Kinematic Viscosity @40°C | ASTM D445 | cSt | 38 |
| Kinematic Viscosity @100°C | ASTM D445 | cSt | 7.5 |
| Viscosity Index | ASTM D2270 | | 170 |
| Flash Point, COC | ASTM D92-05A | °C | > 195 |
| Pour Point | ASTM D97 | °C | < -45 |

Typical properties are typical of those obtained with normal production tolerance and do not constitute a specification.

All the information contained in this document is considered accurate as of date of printing and no warranty of representation, expressed or implied is made as to the accuracy of the data and information in this publication. The information contained herein is subject to change without notice.