

OWS ATF Universal

Multi-Functional Universal Automatic Transmission Fluid

OWS ATF Universal is a HC-synthetic based Automatic Transmission Fluid (ATF) specially developed for a broad usage spectrum in automatic transmissions, power steering units and hydraulic drives.

OWS ATF Universal is manufactured using the highest quality HC-Synthetic base stocks and state of the art Überclean® additive technology. This ensures a finished product with an unmatched performance level.

OWS ATF Universal fulfills or exceeds the following specifications:

Dexron III H	Voith H55.6335.xx / H55.6336.xx
Aisin Warner JWS 3309 / 3314	Volvo 973341
Allison C-4	VW TL 52 162 / G 055 025
BMW LA-2634 / LT-71141 / ETL 7045 E	ZF TE-ML 02F, 04D , 11B, 14B/C, 16L, 17C
Ford M2C195-A / M2C202-B / M2C922-A1 / WSS-M2C924-A	MB 236.6 / 236.9 / 236.10 / 236.11
GM 9986195	Mercon / Mercon V
Hyundai / Kia / Mitsubishi SP-II/-III	Nissan Matic-D / J / K
MAN 339 Type V1 / V2 / Z2 / Z3	Toyota T-IV

Test	Method	Unit	Result
Density @15°C	ASTM D4052	kg / L	0.850
Kinematic Viscosity @40°C	ASTM D445	cSt	29.4
Kinematic Viscosity @100°C	ASTM D445	cSt	6.1
Viscosity Index	ASTM D2270		161
Flash Point, COC	ASTM D92-05A	°C	> 210
Pour Point	ASTM D97	°C	< -45

Typical properties are typical of those obtained with normal production tolerance and do not constitute a specification. All the information contained in this document is considered accurate as of date of printing and no warranty of representation, expressed or implied is made as to the accuracy of the data and information in this publication. The information contained herein is subject to change without notice.