

OWS ATF Ultimate

Multi-Functional Universal Automatic Transmission Fluid of the latest Dexron VI Standard

OWS ATF Ultimate is a premium fully synthetic Automatic Transmission Fluid (ATF) specially developed to in accordance to the latest DEXRON VI standard.

OWS ATF Ultimate is manufactured using the highest quality Synthetic base stocks and state of the art Überclean® additive technology. This ensures a finished product with an unmatched performance level.

OWS ATF Ultimate fulfills or exceeds the following specifications:

DEXRON VI
MB 236.41
Daimler-Chrysler ATF+3 / ATF +4
Hyundai SPIV
ZF M1375
BMW ETL 7045 E / ETL 8072 B

Test	Method	Unit	Result
Density @15°C	ASTM D4052	kg / L	0.847
Kinematic Viscosity @40°C	ASTM D445	cSt	29.7
Kinematic Viscosity @100°C	ASTM D445	cSt	6
Viscosity Index	ASTM D2270		153
Flash Point, COC	ASTM D92-05A	°C	> 210
Pour Point	ASTM D97	°C	< -45

Typical properties are typical of those obtained with normal production tolerance and do not constitute a specification. All the information contained in this document is considered accurate as of date of printing and no warranty of representation, expressed or implied is made as to the accuracy of the data and information in this publication. The information contained herein is subject to change without notice.