

OWS CVT-ATF

Fully Synthetic Automatic Transmission Fluid for use in modern CVT (Continuous Variable Transmission)

OWS CVT-ATF is a fully synthetic high-performance ATF based on the latest generation of synthetic base stocks and OWS Überclean® additive technology.

OWS CVT-ATF is specially developed for use in modern CVTs as per manufacturer`s instruction.

OWS CVT-ATF fulfills or exceeds the following specifications:

Audi / VW G 052 180	Kia / Hyundai CVTF
BMW / Mini EZL 799	MB 236.20
Chrysler / Dodge NS-2 / CVTF+4	Mitsubishi CVTF-J1
Daihatsue TC	Nissan NS-2
Ford CVT23 / CVT30 / Mercon C	Toyota TC
GM / Saturn DEX-CVT	Subaru NS-2 / CVTF
Honde HMMF	Suzuki TC / NS-2 / CVT Green 1

Test	Method	Unit	Result
Density @15°C	ASTM D4052	kg / L	0.850
Kinematic Viscosity @40°C	ASTM D445	cSt	35.0
Kinematic Viscosity @100°C	ASTM D445	cSt	7.25
Viscosity Index	ASTM D2270		178
Flash Point, COC	ASTM D92-05A	°C	>210
Pour Point	ASTM D97	°C	<-50

Typical properties are typical of those obtained with normal production tolerance and do not constitute a specification.

All the information contained in this document is considered accurate as of date of printing and no warranty of representation, expressed or implied is made as to the accuracy of the data and information in this publication. The information contained herein is subject to change without notice.