

OWS Synthotec SAE 0W-20

Premium Low Viscosity Fuel Economy Fully Synthetic Engine Oil

OWS Synthotec SAE 0W-20 is a premium multigrade fully synthetic engine oil with lowered viscosity for enhanced fuel economy properties. It protects against friction heat and corrosion, keeping engines healthy and efficient.

OWS Synthotec SAE 0W-20 is manufactured using specially selected PAO synthetic base stocks and state of the art Überclean® additive technology, reducing carbon and sludge build-up even under severe driving conditions.

OWS Synthotec SAE 0W-20 is optimally suited for hybrid vehicles and other modern vehicles requiring an extremely low viscosity engine oil.

OWS Synthotec SAE 0W-20 fulfills or exceeds the following specifications:

ACEAA5 / B5

API SN

ILSAC GF-5

Test	Method	Unit	Result
Density @15°C	ASTM D4052-09	kg / L	0.857
Kinematic Viscosity @40°C	ASTM D445-10	cSt	45
Kinematic Viscosity @100°C	ASTM D445-10	cSt	8.4
Viscosity Index	ASTM D2270-04		167
Flash Point, COC	ASTM D92-05A(10)	°C	> 210
Pour Point	ASTM D97-09	°C	< -42

Typical properties are typical of those obtained with normal production tolerance and do not constitute a specification.

All the information contained in this document is considered accurate as of date of printing and no warranty of representation, expressed or implied is made as to the accuracy of the data and information in this publication. The information contained herein is subject to change without notice.